

EM-8000C

MULTI-PARAMETER PATIENT MONITOR

EM-8000C multi-parameter patient monitor is a robust patient monitor, small enough to move around, yet flexible enough to adapt to your particular needs. With a variety of optional extras, including arrhythmia and ST analysis, EtCO₂ measurement and double IBP, EM-8000C multi-parameter patient monitor is configurable to suit your requirements. Purchase only the advanced features that you need and nothing more. With NIBP recall and extensive data storage capability, EM-8000C multi-parameter patient monitor is particularly well-suited for use in peri-anesthesia and critical care environments. Rich in functions, conveniently adaptable and pleasingly affordable, EM-8000C multi-parameter patient monitor may be just the monitor for your department.

Features & Benefits:

- 6 Standard parameters: ECG, RESP, NIBP, SPO₂, 2-TEMP, PR/HR.
- 12.1" high resolution color TFT LCD display.
- Real time S-T segment analysis, pace-maker detection.
- Indication of Incorrect manipulation and malfunction analysis.
- Patient info input management function.
- Multi-lead ECG waveforms display in phase.
- Large volume of tabular and graphic trends information storage and easy to recall.
- Capture dynamic waveforms.
- Efficient resistance to interference of defibrillator and HF knife.
- UP to 2 hours working capacity of built-in rechargeable battery.
- Unique accessory management cabinet.
- Networking capacity.
- Option: IBP, ETCO₂ and 2-IBP.





EM-8000C


Multi-parameter Patient Monitor

Monitor ECG, SpO₂, NIBP, RESP, TEMP, PR and HR.

EASTMED is one of the biggest medical and healthcare product manufacturers in China.

Range of product: Patient monitor, Pulse oximeter, Blood pressure monitor, Thermometer, Fetal Doppler, UV radiation, etc.

The whole production line is medical CE certified and mostly FDA certified.



TECHNICAL SPECIFICATIONS	
<p>Quality Standards and Classification</p> <p>CE, ISO13485 SFDA: Class II b Anti-electroshock degree: Class I equipment (internal power supply) TEMP/SpO₂/NIBP: BF ECG/Resp: CF</p> <p>Application Range</p> <p>Adult/Pediatric/Neonatal/Medicine/Surgery/ Operating Room/ICU/CCU</p> <p>Display</p> <p>12.1" real color TFT screen</p> <p>Environment</p> <p>Operating environment : Temperature: 0 ~ 40 C Humidity: 15% ~ 80% Pressure: 86.0 kPa ~ 106.0kPa Transport and Storage environment : Temperature: -20 ~ 55 C Humidity: 10% ~ 90% Pressure: 86.0 kPa ~ 106.0kPa</p> <p>Power Requirements</p> <p>AC: 100 ~ 240V, 50Hz/60Hz DC: Built-in rechargeable battery Battery: 11.1V 24wh Li-ion battery 2h operating after full charge 5min operating after low battery alarm</p> <p>Dimension and Weight</p> <p>Equipment: 310mm × 150mm × 275 mm; 4.5 kg Package: 380mm × 350 mm × 300mm; 6.3 kg</p> <p>Date Storage</p> <p>Trend diagram/table: 720h NIBP review: 10000 events Wave review: 12h Alarm review: 200 alarm events Support drug concentration titration analysis</p>	<p>ECG</p> <p>5 Leads: RA, LA, LL, RL, V Lead mode: I, II, III, AVR, AVL, AVF, V Gain: × 1.25mm/mV, 2.5mm/mV, 5.0mm/mV, 10mm/mV, 20mm/mV (error ≤ 5%) Sweep speed: 6.25mm/s, 12.5mm/s, 25mm/s, 50mm/s (error ± 10%) Bandwidth: Surgery 1 ~ 25 Hz Monitor 0.5 ~ 40 Hz Diagnostic 0.05 ~ 130 Hz Sensitivity: >200 μ V P-P CMRR: ≥ 112dB Differential Input Impedance: >5M ohm Electrode Offset Potential: ±300mV Polarization Voltage: ≥ ± 500mV Input Impedance: ≥ 5 M Calibration Voltage: 1mV ± 5%</p> <p>ST Segment</p> <p>ST Segment Range: -2.0mV ~ +2.0mV Accuracy: 0.02mV</p> <p>NIBP</p> <p>Method: Oscillometry Measure mode: Manual, Auto, STAT Measure interval in auto mode: 1~5/10/15/30/60/90/120/180/240/480min Measure period in STAT mode: 5min Pulse rate range: 40 ~ 240bpm Measure & alarm range: Adult SYS 40 ~ 280mmHg DIA 10 ~ 220mmHg MEAN 20 ~ 240mmHg Pediatric SYS 40 ~ 220mmHg DIA 10 ~ 160mmHg MEAN 20 ~ 170mmHg Neonatal SYS 40 ~ 135mmHg DIA 10 ~ 100mmHg MEAN 20 ~ 110mmHg</p> <p>Static pressure measurement Range: 0 ~ 300mmHg Accuracy: ± 3mmHg Resolution: 1mmHg Accuracy: Max. Mean Error: ± 5mmHg Max. Standard Deviation: 8mmHg Overpressure protection: Adult 300mmHg Pediatric 240mmHg Neonatal 150mmHg</p>
	<p>SpO₂</p> <p>Measurement range: 0 ~ 100% Resolution: 1% Accuracy: 70% ~ 100% ± 2% 40% ~ 69% ± 3%</p> <p>Pulse Rate</p> <p>Measure/alarm range: 20 ~ 300bpm Resolution: 1bpm Accuracy: ± 3bpm</p> <p>RESP</p> <p>Method: impedance between RA-LL Resp Impedance range: 0.3 ~ 3 Ω Base Impedance range: 200 Ω ~ 4000 Ω Bandwidth: 0.3 ~ 2.5Hz Gain: × 0.25, × 0.5, × 1, × 2, × 4 Resp rate: Measurement Range Adult 0 ~ 120BrPM Neonatal/Pediatric 0 ~ 150BrPM Resolution: 1BrPM Accuracy: 7 ~ 150BrPM (± 2BrPM) 0 ~ 6BrPM (unspecified) Apnea Alarm: 10 ~ 40s</p> <p>TEMP</p> <p>Channel 2 Measure & alarm range: 0 ~ 50 C Resolution: 0.1 C Accuracy (no sensor): ±0.1 C (0~50 C)</p> <p>Standard accessories</p> <ul style="list-style-type: none"> ● NIBP cuff & tube ● ECG cable & electrodes ● SpO₂ sensor ● TEMP probe ● Lithium-ion battery ● Power cable ● Operator's manual <p>Optional accessories</p> <ul style="list-style-type: none"> ● Touch screen ● Trolley bracket ● Hanging bracket ● Monitor recorder ● Vehicle-mounted power supply

NOTE: The specifications are subject to changes without prior notice.

AUTHORIZED AGENT

SHENZHEN EAST MEDICAL TECHNOLOGY CO.,LTD

Add: 190# longping Road, Huate Industrial Zone, longgang District, Shenzhen, Guangdong China 518116

Tel: 0755-33275355; Fax: 0755-22658200

Mobile/Whatsapp: 0086-13528424305 skype: east-medical

www.east-medical.com