



Caretium

ISO 13485:2003(04708Q10000157)
ISO 9001: 2008(04708Q10163R1S)

XC-A30

● ESR Analyzer





XC-A30

● ESR Analyzer



Features

- Random access
- Up to 30 samples can be scanned simultaneously
- Throughput: up to 60 samples /hour
- Temperature compensation refer to 18 °C according to Westergren method
- ESR curve display and print-out
- Touch screen , large LCD display
- Built-in internal thermal recorder

Specifications

Area of application	Erythrocyte sedimentation rate analysis
Measuring principle	Infrared sensor
Reading channels	30 available channels
Loading capability	Up to 30 samples at a time
Loading pattern	Random
Measuring time	30 minutes or 60 minutes selectable
Throughput	Up to 60 samples per hour
Analysis result	In Westergren ESR value (mm / hr)
Temperature compensation	Refer to 18°C automatically (selectable)
Reading resolution	0.2 mm
Reproducibility	< 0.3% or ±2mm /1h
Result resolution	1mm/1h
Blood level range	50mm~64mm
Display	LCD screen

Input	Touch screen
Interface	RS-232 serial port
Print	Internal thermal recorder
Power supply	AC 220V/110V ± 10%, 50/60 Hz, 50W
Operation conditions	Temperature 15°C~32°C Humidity≤85%
Dimension	400mmx300mmx200mm(LxWxH)
Net weight	11.5kg



Global Medical Engineering (BD) Ltd.

Corporate Office: 17/2, Topkhana Road (2nd Floor), Dhaka - 1000, Bangladesh.

Phone: +88 09678020555 **Fax:** +88 02 9576881 **Cell:** +8801404003500

E-mail: info@gmebd.com ; gmebd@hotmail.com **Website:** www.gmebd.com